ELSEVIER

Available online at www.sciencedirect.com
SCIENCE DIRECT®

Discrete Applied Mathematics 131 (2003) 691–693

DISCRETE APPLIED MATHEMATICS

www.elsevier.com/locate/dam

Author index to volume 131

Bang-Jensen, J. and S. Thomassé, Highly connected hypergraphs containing no two edge-disjoint spanning connected subhypergraphs (2) 555–559
Bang Le, V.-B., see H.-O. Le (1) 199–212
Bodlaender, H.L., R.B. Tan and J. van Leeuwen, Finding a Δ-regular supergraph of minimum order (1) 3– 9
Boliac, R. and V.V. Lozin, An augmenting graph approach to the stable set problem in P_5-free graphs (3) 567–575
Boros, E., K. Elbassioni, V. Gurvich and L. Khachiyan, An inequality for polymatroid functions and its applications (2) 255–281
Bouchitté, V. and I. Todinca, Approximating the treewidth of AT-free graphs (1) 11– 37
Brandstädt, A., C.T. Hoàng and V.B. Le, Stability number of bull- and chair-free graphs revisited (1) 39– 50
Brešar Boštjan, W. Imrich and Sandi Klavar, Fast recognition algorithms for classes of partial cubes (1) 51– 61

Cai, L., The complexity of the locally connected spanning tree problem (1) 63– 75
Čenek, E. and L. Stewart, Maximum independent set and maximum clique algorithms for overlap graphs (1) 77– 91
Chepoi, V. and F. Dragan, Finding a central vertex in an HHD-free graph (1) 93–111
Cohen, G., S. Encheva, S. Litsyn and H.G. Schaathun, Erratum to "Intersecting codes and separating codes" [Discrete Applied Mathematics 128 (2003) 75–83] (3) 689–690
Connamacher, H.S. and A. Proskurowski, The complexity of minimizing certain cost metrics for k-source spanning trees (1) 113–127
Courcelle, B. and R. Vanicat, Query efficient implementation of graphs of bounded clique-width (1) 129–150

Dahlhaus, E., P. Dankelmann, W. Goddard and H.C. Swart, MAD trees and distance-hereditary graphs (1) 151–167
Danilov, V.I., G.A. Koshevoy and C. Lang, Gross substitution, discrete convexity, and submodularity (2) 283–298
Dankelmann, P., see E. Dahlhaus (1) 151–167
Desai, M.P., H. Narayanan and S.B. Patkar, The realization of finite state machines by decomposition and the principal lattice of partitions of a submodular function (2) 299–310
Dragan, F., see V. Chepoi (1) 93–111
Durand, S., Finding sharper distinctions for conditions of transitivity of the majority method (3) 577–595

Elbassioni, K., see E. Boros (2) 255–281
Encheva, S., see G. Cohen (3) 689–690

Fernandez de la Vega, W. and M. Lamari, The task allocation problem with constant communication (1) 169–177
Fiorini, S. and P. Fishburn, Facets of linear signed order polytopes (3) 597–610

doi:10.1016/S0166-218X(03)00565-1

Fishburn, P., see S. Fiorini (3) 597–610
Fleischer, L. and S. Iwata, A push-relabel framework for submodular function minimization and applications to parametric optimization (2) 311–322
Fomin, F.V. and D.M. Thilikos, On the monotonicity of games generated by symmetric submodular functions (2) 323–335
Frank, A. and L. Szegő, Constructive characterizations for packing and covering with trees (2) 347–371
Frank, A. and T. Király, Combined connectivity augmentation and orientation problems (2) 401–419
Frank, A., Restricted t-matchings in bipartite graphs (2) 337–346
Frank, A., T. Király and M. Kriesell, On decomposing a hypergraph into k connected sub-hypergraphs (2) 373–383
Frank, A., T. Király and Z. Király, On the orientation of graphs and hypergraphs (2) 385–400
Fu, T.-S. and K.-S. Lin, Lattice hypercube designs (3) 673–680
Fujishige, S., Foreword (2) 253–254

Ge, G. and A.C.H. Ling, A new construction for Z-cyclic whist tournaments (3) 643–650
Gebremedhin, A.H., I.G. Lassous, J. Gustedt and J.A. Telle, Graph coloring on coarse grained multicomputers (1) 179–198
Goddard, W., see E. Dahlhaus (1) 151–167
Gurvich, V., see E. Boros (2) 255–281
Gustedt, J., see A.H. Gebremedhin (1) 179–198

Hoàng, C.T., see A. Brandstädt (1) 39– 50

Imrich, W., see Boštjan Brešar (1) 51– 61
Iwata, S., see L. Fleischer (2) 311–322

Jordán, T., On minimally k-edge-connected graphs and shortest k-edge-connected Steiner networks (2) 421–432

Kashiwabara, K. and T. Takabatake, Polyhedra with submodular support functions and their unbalanced simultaneous exchangeability (2) 433–448
Kashiwabara, K. and Y. Okamoto, A greedy algorithm for convex geometries (2) 449–465
Khachiyan, L., see E. Boros (2) 255–281
Király, T., see A. Frank (2) 373–383
Király, T., see A. Frank (2) 385–400
Király, T., see A. Frank (2) 401–419
Király, Z., see A. Frank (2) 385–400
Klavar, Sandi, see Boštjan Brešar (1) 51– 61
Koshevoy, G.A., see V.I. Danilov (2) 283–298
Kratsch, D., Preface (1) 1– 1
Kriesell, M., see A. Frank (2) 373–383

Lamari, M., see W. Fernandez de la Vega (1) 169–177
Lang, C., see V.I. Danilov (2) 283–298
Lassous, I.G., see A.H. Gebremedhin (1) 179–198
Le, H.-O., V.-B. Bang Le and H. Müller, Splitting a graph into disjoint induced paths or cycles (1) 199–212
Le, V.B., see A. Brandstädt (1) 39– 50
Lin, K.-S., see T.-S. Fu (3) 673–680
Lin, Y.-B., Z. Miller, M. Perkel, D. Pritikin and I.H. Sudborough, Expansion of layouts of complete binary trees into grids (3) 611–642
Ling, A.C.H., see G. Ge (3) 643–650
Litsyn, S., see G. Cohen (3) 689–690
Lozin, V.V., see R. Boliac (3) 567–575

Miller, Z., see Y.-B. Lin (3) 611–642
Mizuki, T., H. Shizuya and T. Nishizeki, Characterization of optimal key set protocols (1) 213–236
Müller, H., see H.-O. Le (1) 199–212
Murota, K. and A. Shioura, Quasi M-convex and L-convex functions—quasi-convexity in discrete optimization (2) 467–494
Murota, K. and A. Tamura, New characterizations of M-convex functions and their applications to economic equilibrium models with indivisibilities (2) 495–512

Nakamura, M., see Y. Okamoto (2) 523–533
Narayanan, H., A note on the minimization of symmetric and general submodular functions (2) 513–522
Narayanan, H., see M.P. Desai (2) 299–310
Narayanan, H., see S.B. Patkar (2) 535–553
Nishizeki, T., see T. Mizuki (1) 213–236

Okamoto, Y. and M. Nakamura, The forbidden minor characterization of line-search antimatroids of rooted digraphs (2) 523–533
Okamoto, Y., see K. Kashiwabara (2) 449–465

Patkar, S.B. and H. Narayanan, Improving graph partitions using submodular functions (2) 535–553
Patkar, S.B., see M.P. Desai (2) 299–310
Peeters, R., The maximum edge biclique problem is NP-complete (3) 651–654
Perkel, M., see Y.-B. Lin (3) 611–642
Pisaruk, N.N., A fully combinatorial 2-approximation algorithm for precedence-constrained scheduling a single machine to minimize average weighted completion time (3) 655–663
Pritikin, D., see Y.-B. Lin (3) 611–642
Proskurowski, A., see H.S. Connamacher (1) 113–127

Rigo, M., The commutative closure of a binary slip-language is context-free: a new proof (3) 665–672

Schaathun, H.G., see G. Cohen (3) 689–690
Shioura, A., see K. Murota (2) 467–494
Shizuya, H., see T. Mizuki (1) 213–236
Stewart, L., see E. Čenek (1) 77– 91
Sudborough, I.H., see Y.-B. Lin (3) 611–642
Swart, H.C., see E. Dahlhaus (1) 151–167
Szegő, L., see A. Frank (2) 347–371

Takabatake, T., see K. Kashiwabara (2) 433–448
Tamura, A., see K. Murota (2) 495–512
Tan, R.B., see H.L. Bodlaender (1) 3– 9
Telle, J.A., see A.H. Gebremedhin (1) 179–198
Thilikos, D.M., see F.V. Fomin (2) 323–335
Thomassé, S., see J. Bang-Jensen (2) 555–559
Todinca, I., see V. Bouchitté (1) 11– 37

Vanicat, R., see B. Courcelle (1) 129–150
van Leeuwen, J., see H.L. Bodlaender (1) 3– 9

Woeginger, G.J., On the approximability of average completion time scheduling under precedence constraints (1) 237–252

Yan, W. and F. Zhang, Heredity of the index of convergence of the line digraph (3) 681–688

Zhang, F., see W. Yan (3) 681–688